

# V\_line

VIDEO BY LAWO



SMART  
POWERFUL  
**ULTRA-COMPACT**



## V\_\_line

INTRODUCTION

### VIDEO DONE THE SMART WAY

The video broadcast tools of the V\_\_line are designed to support your workflow and bring you previously unknown efficiency. Leaving the established path of modular systems, Lawo's video solutions do things differently and – more importantly – they do them in a smart way. Lawo's V\_\_line products not only bring major reductions in space and weight, they also reduce cabling effort and the overall complexity of video broadcast installations. Despite the units' comprehensive feature set – which with standard technology would require a full rack of equipment – their browser-based GUI allows easy and intuitive operation. As a result, V\_\_line devices represent significant savings in both CAPEX and OPEX costing. Designed and engineered by video experts, Lawo's V\_\_line products provide excellent production quality – simply and in a smart package.

The Lawo V\_\_line currently consists of  
V\_\_pro 8 – the complete 8 channel video processing toolkit (p. 4)  
V\_\_remote 4 – the IP remote production solution (p. 14)  
V\_\_fp 1 – optional hardware control and monitoring panel  
for V\_\_pro 8 and V\_\_remote 4 (p. 9)

For information about the V\_\_matrix software-defined routing, processing and multiviewing platform please refer to the dedicated V\_\_matrix brochure.

PROUDLY SUPPORTING



# V\_\_pro8

THE COMPLETE 8 CHANNEL VIDEO PROCESSING TOOLKIT

# V\_\_pro8

THE COMPLETE 8 CHANNEL VIDEO PROCESSING TOOLKIT



## CLOSING THE GAP BETWEEN VIDEO AND AUDIO

Conceptually, the V\_\_pro8 resembles a bridge builder. It is a compact, fully digital, 8-channel video processor comprising all of the glue features usually needed in the broadcast production workflow. Combining video and audio management in a single tool guarantees maximum efficiency and greatest operating safety, with significantly reduced space, wiring and cost.

### MAIN BENEFITS

- Increased ease-of-use
- Major space reduction
- Reduced cabling & system complexity
- Swiss-knife style processing toolkit
- Increased workflow efficiency
- Reduced costs

## FOR PERFECT SYNCHRONIZATION: INTEGRATING DIFFERENT SIGNAL WORLDS

The V\_\_pro8 is the perfect tool to connect different video formats as well as to connect between audio and video. High quality format conversion, color correction as well as audio embedding and de-embedding make the V\_\_pro8 a compact and powerful video processor, building bridges between different worlds and formats. A high-density MAD1 audio connection provides efficient video-to-audio bridging within the studio infrastructure. The V\_\_pro8 works as a flexible matrix system: using its 8x8 video matrix and 384x384 audio matrix, it is possible to switch any signal to any other. A modern GUI based on HTML5 provides an ideal interface for easy handling of day-to-day work. Here's how it works: eight high quality 3G SDI de-embedders and a corresponding number of embedders are looped into the eight video signals according to your preferences. This enables any number of audio signals to be used from the video material, and new audio signals to be embedded into the video signal – a simple, reliable and efficient solution.

## AT A GLANCE

- Frame synchronization for each of the 8 channels
- Frame Phaser and Line Phaser mode
- Variable audio and video delays for each channel
- Embedding and de-embedding incl. SRC for each channel
- RGB Color Correction & Proc Amp for each channel
- Up/Down/Cross Format & AR Conversion for two channels
- Two Surround-to-stereo Downmixer per Embedder
- Dolby® E Auto Aligner
- Dolby® E Encoding and Decoding
- Quadsplit Multiviewer
- Waveform and Vectorscope display
- Timecode Insertion, Test Pattern Generator and Video ID Generator for each channel
- Multi-Format Video Output
- Timecode Generator
- Sync Generator
- AV Sync Measurement (Vistek® VALID8 compatible)

### HIGHLIGHTS

#### POWERFUL TOOLS FOR VIDEO PROCESSING

- VIDEO/AUDIO ROUTER provides an internal 8x8 video routing matrix and a 384x384 audio routing matrix.
- FRAME-SYNCHRONIZER for syncing incoming independent free running signals to the same reference (Blackburst or TriLevel).
- VARIABLE VIDEO & AUDIO DELAYS for compensating latencies and lip-sync matching between incoming or outgoing audio (up to 320ms delay) and video (up to 8 frames delay) signals. AudioFollowVideo delay mode for automatic compensation of internal video latency.
- (DE-) EMBEDDING WITH SRC to embed, de-embed and shuffle any of the 16 audio channels within the 8 SDI input/output streams simultaneously. Audio interfacing to mixing consoles or external audio routers via MADI.
- DOLBY E® AUTO ALIGNER to automatically adjust the timing of Dolby® streams.
- SURROUND DOWNMIX for providing two automated Lawo-quality 5.1/7.1 to stereo downmixes per embedder.
- TIMECODE INSERTION provides selectable ATC LTC/VITC1/VITC2 insertion from an input signal or free run mode or from internal Timecode Generator.
- TEST PATTERN AND VIDEO ID GENERATOR provide video ID insertions (text, source, date, timecode, time of day) and color bar test pattern as well as a selection of audio test tones and AV Sync test pattern.
- THUMBNAIL PREVIEWING to provide motion previews of video signals. The thumbnails are available via IP and can be displayed on the V\_\_pro8 GUI, external master control systems or PCs.



Input/Output thumbnail overview for intuitive signal handling



Easy signal patching via drag and drop



Timing measurement overview for easy timing adjustments

#### OPTIONAL FEATURES


- HIGH-QUALITY UP/DOWN/CROSS & AR FORMAT CONVERTER for 3G/HD/SD-SDI signals to any relevant broadcast format. Multi-format video output: an incoming 1080p signal can be converted to 1080i and 720p at the same time. The next generation motion-adaptive de-interlacing and scaling technology guarantees high image quality.
- QUADSPLIT MULTIVIEWER provides a high quality video and audio monitoring solution with true peak&peak metering, UMD and tally support via the unit's MV video outputs (BNC/Display Port), displaying up to four video sources at the same time. The tally lamps can be controlled via Ember+, offering the possibility to integrate the MV tally in the overall tally system of your studio control system. It supports multiple colors (RGB) for multi tally configurations in enhanced TV productions.
- WAVEFORM AND VECTORSCOPE DISPLAYS enable measuring and monitoring of video signals and evaluation of video adjustments processed within the V\_\_pro8.
- RGB & YUV COLOR-CORRECTION AND PROC-AMP to adjust the video signal to specific color requirements. High-quality algorithms guarantee perfect video signals.
- AV SYNC MEASUREMENT is a high-end measurement tool for managing the precise synchronization of audio and video signals. It can create a V\_\_line sync pattern and read/analyse three types of sync patterns: V\_\_line, EBU and the Vistek® VALID8 pattern. Each input of the V\_\_pro8 can be used to read the incoming VALID signal.
- DOLBY E® ENCODING/DECODING provides up to four instances of fully compatible en/decoding of professional quality multi-channel audio on a single AES3 connection with Dolby E® metadata handling. In combination with the unit's Dolby E® Auto Aligner, the V\_\_pro8 becomes the perfect transmission path gateway for multi-channel productions.



Production quality RGB & YUV color correction



Waveform display and aspect ratio settings





AV sync test for easy AV sync measurement

## APPLICATIONS



### THE V\_\_pro8 IN ACTION

#### SIGNAL PROCESSING/GLUE IN OB TRUCKS AND STUDIOS



### THE V\_\_pro8 IN ACTION

#### BUILDING A SMART ENG VEHICLE



## INTERACTION

### HIGH USABILITY, INTUITIVE CONTROLS

Innovative functions are only useful in combination with user-friendly controls. Consequently, the V\_\_pro8 provides three convenient ways to control the device:

### WEB-GUI

The V\_\_pro8 can be configured via an easy-to-understand HTML5-based touch screen interface that runs directly within the web browser. No software installation is needed. As a result, you benefit not only from state-of-the-art user-guidance, but also from elegant animations and many, practical features such as the video channel preview on your GUI. In addition, the web-based approach enables the user to access all V\_\_line devices from anywhere within the network — a feature especially useful in bigger set-ups or in outside broadcast productions with long-distance links.

### Ember+ CONTROL

The V\_\_pro8 fully supports the Ember+ protocol, enabling the device to be controlled by external master control systems like BFE's KSC, Axon's Cerebrum or Lawo's Virtual Studio Manager. This allows operators to easily access multiple device parameters along with other routing parameters of the broadcast installation via a single, integrated interface. In addition, they get access to the V\_\_pro8's thumbnails and peak meters within the VSM desktop environment.

### V\_\_fp1 FRONT PANEL

In addition to the Web GUI, the V\_\_pro8 can be equipped with an optional V\_\_fp1 hardware control panel for direct configuration and operation, including switch panel and shot box functionality. It features a high-res OLED color display for showing the configuration menu and real-time viewing of video sources. In combination with the large rotary encoder and a Return/Cancel button this allows quick and easy set-up on-site. Ten quick-selection buttons for switching sources, a front-panel headphones connector for audio monitoring and an USB port for saving and loading of configurations complete the V\_\_fp1 user interface.



- 1 Main Menu Bar
- 2 Monitoring area (e.g. audio metering & video monitoring)
- 3 Sub menu bar
- 4 Setup area



# V\_\_pro8

## INTERACTION

### QUADSPLIT MULTIVIEWER

The integrated Quadsplit Multiviewer provides a high-quality video and audio monitoring solution via the V\_\_pro8's MV video output (BNC/DisplayPort), displaying up to four video sources at the same time. The audio meters feature absolutely precise PPM and true peak PPM metering and can be positioned as an overlay, inside or outside of the video windows. The configurable meter scales provide user-defined ballistics of the audio bargraphs and a user-defined safe operation area. Peak hold can be set to manual or auto mode. The audio scales can be defined as dBFS, BBC, Nordic or DIN. UMD and tally support complete the monitoring options of the V\_\_pro8's Quadsplit Multiviewer.

The tally lamps can be controlled via Ember+, offering the possibility to integrate the MV tally in the overall tally system of your studio control system. It supports multiple colors (RGB) for multi tally configurations in enhanced TV productions.




- 1 SDI I/Os depending on PPM assignment
- 2 Embedded audio channels
- 3 Peak hold
- 4 Icon for SDI audio source (Input/Output)
- 5 Icon Audio not assigned
- 6 Icon None Mode (PPM is in normal mode)
- 7 Icon True Peak (PPM is in True Peak Mode)
- 8 Audio Meter Type
- 9 Tally Lamps


### V\_\_pro8 – FRONT VIEW



### V\_\_pro8 with V\_\_fp 1



### V\_\_pro8 – REAR VIEW



- 1 Optical MADI ports (2x In/2x Out)
- 2 Default IP / Clear settings button
- 3 Status LEDs (Status, PSU 1/2)
- 4 USB Port (save & load config)
- 5 Headphones output (audio monitoring)
- 6 Return/Cancel button
- 7 OLED Display (setup & video monitoring)
- 8 Rotary control (selection & setup)
- 9 Quick select buttons (e.g. menu delegation & video monitoring)
- 10 Optical MADI ports (2x In/2x Out)
- 11 Default IP / Clear settings button
- 12 Status LEDs (Status, PSU 1/2)
- 13 8x SDI Inputs (3G/HD/SD)
- 14 8x SDI Outputs (3G/HD/SD)
- 15 Quadsplit MV Output (Display Port 3G & SDI 3G/1080i)
- 16 Optical MADI ports (2x In/2x Out)
- 17 2x 1 Gbit Ethernet (Control & Management)
- 18 Video Ref. Input & Loop Thru (BB or TriLevel)
- 19 Video Ref. Output (BB or TriLevel)
- 20 WordCLK I/O
- 21 Redundant Power Supplies

### SPECIFICATIONS

#### VIDEO INTERFACES

- VIDEO SIGNAL INPUT/OUTPUT: 8x 3G/HD/SD-SDI inputs via BNC connector, 8x 3G/HD/SD-SDI outputs via BNC connector, 1x 3G/1080i MV/QS output via BNC, DisplayPort for local MV/QS monitoring
- VIDEO REFERENCE SIGNAL INPUT/OUTPUT: BB/Tri-Level, Loop thru, BB/Tri-Level output via BNC connector
- VIDEO STANDARDS:
  - 2.97Gbps Video Standards (1080p):
    - 1080p 60Hz SMPTE-424M, 425M Level A & Level B
    - 1080p 59.94Hz SMPTE-424M, 425M Level A & Level B
    - 1080p 50Hz SMPTE-424M, 425M Level A & Level B
  - 1.485Gbps Video Standards (HD):
    - 1080i 60Hz SMPTE-274M(4),-292M(D)
    - 1080i 59.94Hz SMPTE-274M(5),-292M(E)
    - 1080i 50Hz SMPTE-274M(6),-292M(F)
    - 1080p 30/29.97/25/24/23.976sf
    - 1080p 30Hz SMPTE-274M(7)-292M(G)
    - 1080p 29.97Hz SMPTE-274M(8)-292M(H)
    - 1080p 25Hz SMPTE-274M(9)-292M(I)
    - 1080p 24Hz SMPTE-274M(10)-292M(J)
    - 1080p 23.976Hz SMPTE-274M(11)-292M(K)
    - 720p 60Hz SMPTE-296M(1),-292M(L)
    - 720p 59.94Hz SMPTE-296M(2),-292M(M)
    - 720p 50Hz SMPTE-296M(2),-292M(M)
  - 270Mbps Video Standards (SD):
    - 576i 16:9 and 4:3 SMPTE-259M(C)
    - 480i 16:9 and 4:3 SMPTE-259M(C)
- VIDEO REFERENCE: Analog Genlock High definition tri-level sync SMPTE-274M/296M or SD 1V BB SMPTE-170M/318M or SDI
- RETURN LOSS: SD: > 15dB; HD: > 15dB; 3G-HD: >15dB 5MHz-1.485GHz, >10dB 1.485GHz-2.97GHz
- CABLE LENGTH: SD: >350m (using Belden1694A), HD: >180m (using Belden 1694A), 3G-HD: >120m (using Belden1694A)
- VIDEO RESOLUTION: 10 bit 4:2:2

#### AUDIO INTERFACES

- AUDIO SIGNAL INPUT/OUTPUT: 2x MADI/AES10 optical in/out via LC connector front/rear (redundant mode selectable); SDI embedded Audio via BNC connector, Ethernet
- AUDIO REFERENCE SIGNAL INPUT/OUTPUT: BB/Tri-Level, WordCLK input via BNC connectors (for audio phase alignment only), WordCLK output via BNC connectors
- AUDIO STANDARDS: SMPTE 299/48, MADI/AES10
- AUDIO RESOLUTION: 24 bit

#### METADATA

- ATC (LTC, VITC1, VITC2) SMPTE12M-2, Binary group data SMPTE 309, AFD SMPTE2016, Closed-Caption SMPTE334, VBI data services /DTV descr. SMPTE334, Source-ID OBS-special, Dolby E® Meta data SMPTE2020, ANSI/SCTE 104 SMPTE2010, DVB/SCTE VBI SMPTE2031, Teletext OP-47 (more on request)

#### IP INTERFACES

- GIGABIT ETHERNET: 2x RJ45 100/1000Base-T

#### PROCESSING

- THUMBNAILING & PPM: input/output JPEG thumbnails and PPM data
- AV SYNC (AUDIO/VIDEO): synchronous operation < 2 msec
- VIDEO/AUDIO OUTPUT SYNCHRONIZATION: Genlocked to external clock reference or SDI input
- LATENCY: video processing latency: max. 100 pixels; format conversion: 1 frame; QuadSplit monitoring: 1 frame; audio latency (SRC disabled, synchr. operation): < 2 ms
- OPTIONAL DOLBY E® ENCODING/DECODING: 16 bit/20bit incl. metadata generation according to Dolby® specifications. Flexible license management with up to four licenses per unit (each license can operate either as Encoder or Decoder)

#### MANAGEMENT AND MONITORING

- PROTOCOLS: HTTP, SNMPv1, Ember+
- USER INTERFACES: Embedded HTML5 user interface, front LED status indication, optional V\_\_fp1 control panel, virtual GPUs (via Ember+)

#### ENVIRONMENTAL


- STORAGE TEMPERATURE: -20°C to +70°C (-4°F to +158°F)
- OPERATING TEMPERATURE: 0°C to +40°C (+32°F to +104°F)
- RELATIVE HUMIDITY: < 90% non-condensing
- ELECTROMAGNETIC ENVIRONMENT: E2 (EN55103-1,-2)

#### POWER

- 2x Auto sensing 100 .. 240V VAC power supply 50/60 Hz nominal on IEC connector < 80W

#### FRAME MECHANICS

- DIMENSIONS (H x W x D): 44 mm (1 RU) x 481 mm (19") x 458 mm (18")
- WEIGHT: 4.6 kg (10.2 lb)



# V\_\_remote4

THE IP REMOTE PRODUCTION SOLUTION

## V\_\_remote4

THE IP REMOTE PRODUCTION SOLUTION



### LAW0 V\_\_remote4 – THE ALL-IN-ONE SOLUTION FOR IP-BASED REMOTE PRODUCTIONS

Lawo's V\_\_remote4 is designed to provide a one-box-solution for all the requirements of video and audio signal transport and processing in WAN-based remote productions as well as in standard contribution applications. It includes everything from Video-over-IP coding to various monitoring and processing tools. All designed for one purpose: to provide a tool that increases the flexibility of any broadcast application, while saving valuable rack-space, set-up time and production costs. With its virtual cabling capability, V\_\_remote4 immediately brings IP infrastructure advantages and cost savings, providing an unparalleled degree of flexibility and scalability.

#### MAIN BENEFITS

- Immediate cost savings by remote production
- New flexibility through IP infrastructure
- Unprecedented scalability
- Perfect tool for transition from SDI to the IP world
- Enables new and more efficient production workflows
- IP designed for video engineers, not for IT departments
- SMPTE2022-6/-7 compliant
- VSF TR-01/-03/-04 compliant\*
- J2K compression on board
- VC-2 for mezzanine compression, allowing 4x 3G on a single 10GE link
- Following AIMS roadmap

PROUDLY SUPPORTING



\* full compatibility with future SW release

# V\_\_remote4

## HIGHLIGHTS

## HIGHLIGHTS

### REMOTE PRODUCTION FOR REALIZING TOMORROW'S VISIONS ALREADY TODAY

With the performance and maturity of today's IP network technology, video-, audio- and control-over-IP are becoming the solution of choice for many applications. In remote live production, which is increasingly regarded as one of the next major steps in the evolution of broadcast production, IP is becoming a fundamental requirement. Getting reliable, low latency and high-quality video from venues back to studios at reasonable cost is an absolute necessity for this.

The Lawo V\_\_remote4 is the ideal tool for achieving this vision of IP-based remote broadcast production today. The device combines a bi-directional, four-channel Video-over-IP interface, four local SDI inputs and outputs, along with all the processing tools usually needed when contributing video and audio via WAN or LAN to a broadcast production.

### AT A GLANCE

- Multiple Video-over-IP Encoding and Decoding: 4x/4x Raw/VC-2\*; 4x/4x JPEG2000\*\* (multicast/unicast); 1x H.264\* (multicast/encoding only)
- Integrated switch fabric, switching capacity 40Gbps, 2x 10Gbit Ethernet and 4x 1Gbit Ethernet (2x incl. PoE)
- Frame synchronization for each channel
- Frame Phasing, Line Phasing
- Variable audio and video delays for each channel
- Embedding and de-embedding incl. SRC for each channel
- RGB Color Correction & Proc Amp for each channel\*
- Two Surround-to-stereo Downmixers per Embedder
- Dolby® E Auto Aligner\*
- Quadsplit Multiviewer\*
- Waveform and Vectorscope display\*
- Timecode Insertion, Test Pattern Generator and Video ID Generator for each channel
- Timecode Generator
- Sync Generator, PTP Grandmaster with Ref GM function\*
- AV Sync Measurement\* (Vistek® VALID8 compatible)
- Network Sounding\*

### VIDEO-OVER-IP CONTRIBUTION VIA WAN

The Lawo V\_\_remote4 provides four 3G/HD/SD SDI inputs and four 3G/HD/SD SDI outputs for interfacing to external video equipment. The device is designed to convert these signals into IP streams and vice versa. These streams can be transported via standard Layer 3 IP LANs or WANs. V\_\_remote4 provides parallel encoding in multiple streaming formats, making the same signal available to different applications – e.g. RAW for local production, JPEG2000 for remote sites and H.264 for monitoring applications. The IP-based approach allows easy signal routing via Lawo's VSM control and monitoring system or via other external master control systems. No rewiring is needed as long as all devices are connected to the network. Since the device is based on a real network technology with multi-cast capability, it allows easy transmission of signals to multiple outputs within the network.

The V\_\_remote4's coding engines are designed to meet the highest demands in video quality and signal transport reliability. The unit's extremely robust J2K codec (with a special protection algorithm for robust signal transport even on unreliable WAN connections) and its SMPTE2022-7 compatible port redundancy ensure signal availability and quality. Format and quality of the IP video streams can be configured individually to meet the optimal ratio between picture quality, latency and bandwidth. The 6 Ethernet ports are connected to an internal switch allowing to "tunnel" through the 10Gbit any IP traffic such as camera control, RAVENNA streams or even office and internet IP traffic.

### SUPPORTED VIDEO TRANSPORT MODES

- Raw mode for transparent transport of uncompressed, full production quality video with the lowest latency. SMPTE 2022-6\*\*\* compatible. Full code stream bit rates: HD 1.5Gbps, 3G 2.97Gbps
- Ultra low latency mode for transporting production quality video with ultra low latency VC-2 (DiracPro) Codec, end-to-end delay incl. encoding and de-coding <32 video lines
- Low latency mode\*\* for transporting production quality video. JPEG2000 Codec, bit rates: 30Mbps – 250Mbps, end-to-end delay incl. encoding and de-coding <2.5 frames (4x/4x mode: <4 frames). 16 channels of embedded audio.
- MJPEG mode for monitoring and IP-TV applications. MJPEG Encoder, full code stream bit rates typ. 60Mbps, end-to-end delay with V\_\_view\_app <3 frames
- H.264 mode for monitoring applications. H.264 Encoder, full code stream bit rate 8Mbps, up to 10 stream subscribers
- Full support of source-timed frame-accurate switching of SMPTE2022-6 video
- Following AIMS roadmap

### SUPPORTED AUDIO TRANSPORT MODES

- RAVENNA
- AES67
- Embedded SMPTE 2022-6
- Embedded JPEG2000



\* optional feature \*\* 4x J2K Encoding/4x J2K Decoding; when working with 3G signals: 2x J2K Encoding/2x J2K Decoding/J2K not in parallel with VC-2\*\*\* without FEC

### POWERFUL TOOLS FOR VIDEO CONTRIBUTION

- VIDEO/AUDIO ROUTER provides an internal 8x8 video routing matrix (4x SDI + 4x IP) and a 384x384 audio routing matrix.
- INTERNAL SWITCH with 2x 10G Ethernet and 4x 1G Ethernet ports (2x PoE) for any network application.
- IP STREAMING ENGINE for video and audio signals with raw format video encapsulation (SMPTE 2022-6).
- CLEAN SWITCHING supports source-timed frame-accurate switching of SMPTE 2022-6 video
- SYNC-GENERATOR for precise clocking of broadcast infrastructures.
- VIRTUAL BLACKBURST for sync distribution via WAN/LAN.
- 3G CONVERSION down-converts 3G to 1080i for 10GE streaming applications.
- FRAME-SYNCHRONIZER for syncing incoming independent free running signals to the same reference.
- VARIABLE VIDEO & AUDIO DELAYS for compensating latencies and lip-sync matching between incoming or outgoing audio (up to 320ms delay) and video (up to 8 frames delay) signals. In Delay Auto Mode the audio delay can be set to automatically follow the video delay.
- (DE-) EMBEDDING WITH SRC to embed, de-embed and shuffle any of the 16 audio channels within the 8 SDI input/output streams simultaneously. Audio interfacing to mixing consoles or external audio routers via MADI and AES67/RAVENNA.
- SURROUND DOWNMIX for providing two automated Lawo-quality 5.1/7.1 to stereo downmixes per embedder.
- TIMECODE INSERTION provides selectable ATC LTC/VITC1/VITC2 insertion from an input signal or free run mode or from internal Timecode Generator.
- TEST PATTERN AND VIDEO ID GENERATOR provide video ID insertions (text, source, date, timecode, time of day) and color bar test pattern as well as a selection of audio test tones and AV Sync test pattern.
- THUMBNAIL PREVIEWING to provide motion previews of video signals. The thumbnails are available via IP and can be displayed on the V\_\_remote4 GUI, external master control systems or PCs.

### OPTIONAL FEATURES


- VC-2 CODECS\* mezzanine compression for production quality low-latency IP streaming (suitable for multiple coding generations).
- JPEG2000 CODECS\* for production quality, bandwidth-reduced, low latency IP streaming incl. 16 channels of embedded audio (suitable for multiple coding generations).
- H.264 ENCODER\* for IP monitoring applications.
- WAN AUDIO TRANSPORT enables WAN-capable MADI-over-IP audio transport via RAVENNA/AES67 streaming.
- NETWORK SOUNDING for testing the WAN's network performance in order to provide metrics for trouble-shooting and monitoring, e.g. jitter management.
- REF GRANDMASTER generates a PTP for the complete network derived from an incoming video reference signal.
- QUADSPILT MULTIVIEWER provides a high quality video and audio monitoring solution with true peak & peak metering, UMD and tally support via the unit's MV video outputs (BNC/Display Port), displaying up to four video sources at the same time. The tally lamps can be controlled via Ember+, offering the possibility to integrate the MV tally in the overall tally system of your studio control system. It supports multiple colors (RGB) for multi tally configurations in enhanced TV productions.
- WAVEFORM AND VECTORSCOPE DISPLAYS enable measuring and testing of video signals and evaluation of video adjustments processed within the V\_\_remote4.
- RGB & YUV COLOR-CORRECTION AND PROC-AMP to adjust the video signal to specific color requirements. High-quality algorithms guarantee perfect video signals.
- AV SYNC MEASUREMENT is a high-end measurement tool for managing the precise synchronization of audio and video signals. It can create a V\_\_line sync pattern and read/analyse three types of sync patterns: V\_\_line, EBU and the Vistek® VALID8 pattern. Each SDI and IP input of the V\_\_remote4 can be used to read the incoming VALID signal.
- DOLBY E® AUTO ALIGNER to automatically adjust the timing of Dolby® streams.

\* V\_\_remote4 allows the activation of either the VC-2 or JPEG2000 option. No H.264 with VC-2.

## APPLICATIONS


### V\_\_remote4 IN ACTION

#### CONTRIBUTION & REMOTE PRODUCTION



### V\_\_remote4 IN ACTION

#### PLUG & PLAY REMOTE PRODUCTION KIT



#### PLUG & PLAY REMOTE PRODUCTION KIT

Lawo V\_\_remote4 is also available as a stand-alone Plug & Play Remote Production Kit, providing fully-integrated video, audio and intercom transport (via qualified IP WAN connections) for any third-party video and audio equipment. The kit connects up to four camera CCUs via SDI for video and TCP/IP for control, with audio mixers connected via MADI or RAVENNA/AES67. An IP-based Compact Engine with audio I/O and GPIO on the remote site provides no-latency audio monitor mixing, e.g. for IFBs. The unit is operated via Tablet or PC – in addition to the local operation it can be controlled from a remote studio (e.g. via a Lawo mc<sup>2</sup> console). Additional microphone inputs are furnished with A\_\_mic8 Analog-to-IP interfaces. The kit is completely controllable via a VSM control system.



# V\_\_remote4

## INTERACTION

## INTERACTION

### UNIFIED CONTROL FOR IP SIGNAL ROUTING

V\_\_remote4 devices are managed with the Lawo VSM broadcast control and monitoring system. This enables convenient management of all V\_\_line video streams, as well as the audio streams from A\_\_line Audio-to-IP interfaces from one unified control GUI. VSM provides intuitive video and audio stream setup with a routing function that operates just like a standard router control panel. The VSM system hides the complexity of the IP network from the user, and provides immediate advantages: Reconfigure without the need to touch any physical cables, setup streams, and control parameters all with the use of a mouse-click or touch-screen control. In addition, the VSM system also includes a comprehensive range of hardware control panels.



### INTUITIVE DEVICE CONFIGURATION

The Lawo V\_\_remote4 provides three convenient ways to control the device:

#### WEB-GUI

Easy-to-understand HTML5-based touch screen interface with live video monitoring that runs directly within the web browser. The GUI enables the operator to access all V\_\_line devices from anywhere within the network.



#### Ember+ CONTROL

The Ember+ protocol support enables the device to be controlled by external master control systems like BFE's KSC, Axon's Cerebrum or Lawo's Virtual Studio Manager. This allows the building of broadcast installations with an integrated user interface.

#### V\_\_fp 1 FRONT PANEL


The optional V\_\_fp 1 hardware control panel for direct configuration features a high-res OLED color display for showing the configuration menu and real-time viewing of video sources and audio metering, headphones output for audio pre-listen as well as ten quick selection buttons for direct source switching.




### V\_\_remote4 – FRONT VIEW



### V\_\_remote4 with V\_\_fp 1



### V\_\_remote4 – REAR VIEW



- |  |  |
|--|--|
| 1 Optical MADi ports (2x In/2x Out)                              | 13 4x SDI Inputs (3G/HD/SD)                      |
| 2 Default IP button  | 14 4x 1 Gbit Ethernet (2x PoE)                   |
| 3 Status LEDs (Status, PSU 1/2)                                  | 15 Quadsplit MV Output (SDI 3G/1080i)            |
| 4 USB Port (save & load config)                                  | 16 4x SDI Outputs (3G/HD/SD)                     |
| 5 Headphones output (audio monitoring)                           | 17 2x 10 Gbit Ethernet (SFP+)                    |
| 6 Return/Cancel button   | 18 Quadsplit MV Output (Display Port 3G)         |
| 7 OLED Display (setup & video monitoring)                        | 19 2x USB  |
| 8 Rotary control (selection & setup)                             | 20 GPI/O   |
| 9 Quick select buttons (e.g. menu delegation & video monitoring) | 21 Video Ref. Input & Loop Thru (BB or TriLevel) |
| 10 Optical MADi ports (2x In/2x Out)                             | 22 Video Ref. Output (BB or TriLevel)            |
| 11 Default IP button   | 23 WordCLK I/O                                   |
| 12 Status LEDs (Status, PSU 1/2)                                 | 24 Redundant Power Supplies                      |

# V\_remote4

## SPECIFICATIONS

### SPECIFICATIONS

#### VIDEO INTERFACES

- VIDEO SIGNAL INPUT/OUTPUT: 4x 3G/HD/SD-SDI inputs via BNC connector, 4x 3G/HD/SD-SDI outputs via BNC connector, 1x 3G/1080i MV/QS output via BNC, DisplayPort for local MV/QS monitoring
- VIDEO REFERENCE SIGNAL INPUT/OUTPUT: BB/Tri-Level, Loop thru, BB/Tri-Level output via BNC connector, IP
- VIDEO STANDARDS:
  - 2.97Gbps Video Standards (1080p):
    - 1080p 60Hz SMPTE-424M, 425M Level A & Level B
    - 1080p 59.94Hz SMPTE-424M, 425M Level A & Level B
    - 1080p 50Hz SMPTE-424M, 425M Level A & Level B
  - 1.485Gbps Video Standards (HD):
    - 1080i 60Hz SMPTE-274M(4),-292M(D)
    - 1080i 59.94Hz SMPTE-274M(5),-292M(E)
    - 1080i 50Hz SMPTE-274M(6),-292M(F)
    - 1080p 30/29.97/25/24/23.976sf
    - 1080p 30Hz SMPTE-274M(7)-292M(G)
    - 1080p 29.97Hz SMPTE-274M(8)-292M(H)
    - 1080p 25Hz SMPTE-274M(9)-292M(I)
    - 1080p 24Hz SMPTE-274M(10)-292M(J)
    - 1080p 23.976Hz SMPTE-274M(11)-292M(K)
  - 720p 60Hz SMPTE-296M(1),-292M(L)
  - 720p 59.94Hz SMPTE-296M(2),-292M(M)
  - 720p 50Hz SMPTE-296M(2),-292M(M)
- 270Mbps Video Standards (SD):
  - 576i 16:9 and 4:3 SMPTE-259M(C)
  - 480i 16:9 and 4:3 SMPTE-259M(C)
- VIDEO REFERENCE: Analog Genlock High definition tri-level sync SMPTE-274M/296M or SD 1V BB SMPTE-170M/318M or SDI or IP-VideoStream, IEEE1588 PTPv2+RefMaster (SMPTE2059)
- RETURN LOSS: SD: > 15dB; HD: > 15dB; 3G-HD: >15dB 5MHz-1.485GHz, >10dB 1.485GHz-2.97GHz
- CABLE LENGTH: SD: >350m (using Belden1694A), HD: >180m (using Belden 1694A), 3G-HD: >120m (using Belden1694A)
- VIDEO RESOLUTION: 10 bit 4:2:2

#### AUDIO INTERFACES

- AUDIO SIGNAL INPUT/OUTPUT: 2x MADI/AES10 optical in/out via LC connector front (redundant mode selectable); SDI embedded Audio via BNC connector, Ethernet
- AUDIO REFERENCE SIGNAL INPUT/OUTPUT: BB/Tri-Level, WordCLK input via BNC connectors (for audio phase alignment only), WordCLK output via BNC connectors
- AUDIO STANDARDS: SMPTE 299/48, MADI/AES10, RAVENNA/AES67
- AUDIO RESOLUTION: 24 bit

#### METADATA

- ATC (LTC. VITC1, VITC2) SMPTE12M-2, Binary group data SMPTE 309, AFD SMPTE2016, Closed-Caption SMPTE334, VBI data services /DTV descr. SMPTE334, Source-ID OBS-special, Dolby E® Meta data SMPTE2020, ANSI/SCTE 104 SMPTE2010, DVB/SCTE VBI SMPTE2031, Teletext OP-47, User App ID DID C1&C4 (Y-HANC) (more on request)

#### IP INTERFACES

- GIGABIT ETHERNET: 4x RJ45 100/1000Base-T, 2x POE, 2+2 redundant operation selectable\*
- 10G ETHERNET: 2x SFP+, redundant operation selectable
- PROTOCOLS: IPv4/UDP/TCP/RTP/RTCP, ARP, RSTP, LLD P, IGMPv2, DiffservTOS, IEEE1588 PTPv2 (transparent clock)
- VLAN: port-based VLAN1 & VLAN2; assignable management port
- SWITCHING CAPACITY: max. 40Gbps, video & audio content streaming max. 10Gbps

#### PROCESSING

- VIDEO ENCAPSULATION (10 BIT 4:2:2): Raw (uncompressed) encoding and decoding (SMPTE2022-6 vs. RV) or VC-2 (DiracPro-LL) compressed encoding and decoding; JPEG2000 encoding and decoding (VSF-TRO1\* vs. RV)
- SEAMLESS PROTECTION SWITCHING (Hitless Merge, compliant with SMPTE2022-7)
- RAW ENCODING & DECODING: 4x video encoding bitrates 2.5Gbps, 1.25Gbps; latency < 1 line
- JPEG2000 ENCODING & DECODING: 4x encoding / 4x decoding with HD/SD-SDI, 2x encoding / 2x decoding with 3G-SDI; video only encoding bitrates up to 250Mbps; latency 1-2 frames at encoding, 0.5-1 frame at decoding
- H264 ENCODING (8 BIT 4:2:0): 1x video encoding with stereo audio; encoding bitrate fixed 8Mbps

- THUMBNAILING & PPM: input/output JPEG thumbnails and PPM data
- AUDIO ENCAPSULATION: AES67 and RAVENNA audio streams (encoding AM824, decoding L16, L24, AM824); Encoding bitrates stream dependant; Latency synchronous operation < 2msec
- AV SYNC (AUDIO/VIDEO): synchronous operation < 2msec
- VIDEO/AUDIO OUTPUT SYNCHRONIZATION: Genlocked to external clock reference, genlocked to IP PTP master clock-based reference, genlocked to SDI or IP input
- LATENCY: video processing latency: max. 100 pixels; QuadSplit monitoring: 1 frame; audio latency (SRC disabled, synchr. operation): < 2ms

#### MANAGEMENT AND MONITORING

- PROTOCOLS: HTTP, SNMPv1, Ember+, NMOS IS-04/05\*, Syslog
- USER INTERFACES: Embedded HTML5 user interface; optional V\_\_fp 1 control panel
- GPI: physical and virtual GPIs (via Ember+)

#### ENVIRONMENTAL


- STORAGE TEMPERATURE: -20°C to +70°C (-4°F to +158°F)
- OPERATING TEMPERATURE: 0°C to +40°C (+32°F to +104°F)
- RELATIVE HUMIDITY: < 90% non-condensing
- ELECTROMAGNETIC ENVIRONMENT: E2 (EN55103-1,-2)

#### POWER

- 2x Auto sensing 100 .. 240V VAC power supply 50/60Hz nominal on IEC connector < 130W incl. 30W PoE

#### FRAME MECHANICS

- DIMENSIONS (H x W x D): 44 mm (1 RU) x 481 mm (19") x 458 mm (18")
- WEIGHT: 5.1 kg (11.2 lb)



# V\_\_line

V\_\_pro 8

V\_\_remote 4

© 2018 Lawo AG. All rights reserved. Windows is a registered trademark of Microsoft Corporation. Dolby and Dolby E are registered Trademarks of Dolby Laboratories. Other company and product names mentioned herein may be trademarks of their respective owners. Product specifications are subject to change without notice. This material is provided for information purposes only; Lawo assumes no liability related to its use. As of July 2018.

## HEADQUARTERS

Lawo AG  
Rastatt  
GERMANY  
+ 49 7222 1002 0  
sales@lawo.com

## INTERNATIONAL OFFICES

BENELUX	+ 31 6 54 26 39 78
CANADA	+ 1 416 292 0078
CHINA	+ 86 10 6439 2518
NORWAY	+ 47 22 106110
SINGAPORE	+ 65 9818 3328
SWITZERLAND	+ 49 7222 1002 0
USA	+ 1 888 810 4468

## RENTAL SERVICE

+ 49 7222 1002 0  
rental@lawo.com



[www.lawo.com](http://www.lawo.com)

